JAZZ-3204ED

Eco-Solvent / Dye Sublimation Printer (with Four i3200 heads)

QUANTUM Eco-Solvent / Dye Sublimation Ink

C M Y K

Four I3200-E1 Heads

Four I3200-E1 Print Heads Speed	
360x2400dpi - 4pass	84 m²/h
720x1800dpi - 6pass	62 m²/h
720x2400dpi - 8pass	47 m²/h

Our range of wide format inkjet printers matches our knack for engineering and quality with your desire for impeccable performance and careless production. You can produce roll-to-roll indoor prints and long term outdoor signs. Wide applications in light box posters, customized car stickers, background wall cloth, label printing, advertising sign, subway advertising, shopping mall advertising signs etc.


● Technical Specifications

| Model		JAZZ-3204ED
Print Head		Four I3200-E1 Print Heads
Printing Technology		Piezoelectric Inkjet
Acceptable Media	Width	3200mm
	Thickness	Maximum 59 mil(1.5 mm)
	Weight	132.2 lb.(60 kg)
Printing Width		3050mm
Ink Cartridges	Type	Eco Solvent Ink / Dye Sublimation Ink
	Capacity	4*4 CISS (220ml ink cartridge with 1.5L ink tank)
	Color	4 colors (Cyan, Magenta, Yellow, Black)
Printing Resolution		Maximum 2400 dpi
Printing Speed		4pass(360x2400dpi) : 84 sqm/h 6pass(720x1800dpi) : 62 sqm/h 8pass(720x2400dpi) : 47 sqm/h
Media Heating System		Intergrated post heater & Infrared Dryer & Fan system
Interface		USB 2.0
Power Supply		AC 220V ± 10%, 50/60 HZ
Dimensions(with stand)		4545 x 1041 x 1732mm
Weight(with stand)		600kg
Package Dimensions		4800 x 1100 x 850mm
Package Weight		720kg
Environment	Power on	Temperature: 59 ℉ to 90 ℉ [15℃ to 32℃] (68 ℉[20℃] / Humidity: 35 to 80% (no condensation)
	Power off	Temperature: 41 ℉ to 104 ℉ [5℃ to 40℃] / Humidity: 20 to 80% (no condensation)
Accessories		USB cable, media clamp, manual, drain bottle, ink cartridges, RIP software, etc.

THK high-precision mute rail

Equipped with 4pcs authorized I3200-E1 print heads,high precision, high speed, high stability.

High-precision and high-stability tensioning pulley system

Bulky ink bottle with low-ink alarm represents the advanced concept of industrial application

The automatic cleaning assembly adds a single-way valve to increase the stability of the ink supply

Three stage heating system including pre-heater, print heater, and rear heater and platform vacuum system with adjustable power.

New pinch roller structure of three in group brings more stable feeding precision

External power supply, intelligent rolling system.